



# Installation Instructions

## DESCRIPTION

**MFM Roof Deck Tape™** is a self-adhering waterproofing tape composed of a non-slip surfaced film laminated to rubberized asphalt adhesive. The adhesive is protected by a release paper.

## INTENDED USE

MFM Roof Deck Tape is used to tape all seams of a plywood or OSB roof deck, preventing water from entering the structure. Once the seams are taped, the roof may be covered with roofing felt, synthetic or self-adhering underlayment. Should the main roof be damaged, MFM Roof Deck Tape will prevent water from entering the structure between the deck seams

The aggressive *Broad Temperature Spectrum* adhesive used in MFM Roof Deck Tape self-seals around fasteners such as nails, screws and staples. Additionally, it readily sticks to plywood, OSB, rigid foam insulation, metal and other common roof deck materials.

MFM Roof Deck Tape may also be used to prepare a substrate for a self-adhered membrane (such as Peel & Seal™) by taping larger than desired joints and seams.

## INSTALLATION

- Roof deck must be clean and dry.
- Apply in dry weather at recommended temperatures.
- Start at the bottom and work up the roof so that the seams are overlapped like shingles.
- Peel back about 6" - 12" of the release paper, center tape over seam, adhere tape to roof deck and align.
- Continue to peel back the release paper as the tape is unrolled and press tape into place over roof seam.
- Allow 4" - 6" overlaps between pieces of tape. If possible, laps must be made in a "shingle-like" manner so that water flows over the lap not against it.
- Apply firm, uniform pressure with a hand roller to the entire surface of the tape, especially at the seams & overlaps.
- Cover with roofing underlayment or felt within 60 days.

## CAUTION

- Concrete, masonry, DensDeck®, Fiberock® or similar must be fully cured and primed with MFM Prime-A-Seal™, MFM Spray Primer or other asphalt-based primer for satisfactory adhesion.
- Do not apply over uncured solvents, sealants or silicone caulking! It is the installer's responsibility to ensure that all sealants used are compatible with asphalt.

Recommended Application Range	35° F—110° F
Linear Feet per Roll	67'
Linear Feet per Carton	4" = 600' 6" = 400'



MFM Roof Deck Tape meets ASTM D 1970  
 Florida Building Code FL#5229.1  
 Miami-Dade County NOA 06-051807