Safety Data Sheet



Revision Number: 004.0

Issue date: 01/09/201

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

 Product type:
 Joint s

 Restriction of Use:
 None

 Company address:
 Henkel Corporation

 One Henkel Way
 Rocky Hill, Connecticut 06067

OSI Quad Max Window, Door & Siding Sealant Joint sealant, polymer silan-modified None identified Region: Contact infor Telephone: + MEDICAL EM 4608 (toll free

Region:United StatesContact information:Telephone: +1 (800) 624-7767MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCYPhone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

1893977

2. HAZARDS IDENTIFICATION

WARNING:

EMERGENCY OVERVIEW CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. HARMFUL IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	4
SKIN IRRITATION	2
EYE IRRITATION	2A

PICTOGRAM(S)	

Precautionary Statements

Prevention:	Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye and face protection. Wear protective gloves.
Response:	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you
	feel unwell. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	30 - 60

Phthalate ester	Proprietary	5 - 10
Silane derivative	Proprietary	1 - 5
	Proprietary	0.1 - 1
Reactive Silane	Proprietary	0.1 - 1

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

Exposure to moisture during cure will release 1-2% methanol.

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.	
Skin contact:	Wash with soap and water. If skin irritation persists, call a physician. Wipe off paste with paper towel or cloth.	
Eye contact:	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. If symptoms develop and persist, get medical attention.	
Ingestion:	Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a physician.	
Symptoms:	See Section 11.	
Notes to physician:	Treat symptomatically and supportively.	
5. F	FIRE FIGHTING MEASURES	
Extinguishing media:	carbon dioxide, foam, powder, water spray jet, fine water spray	
Special firefighting procedures:	Wear protective equipment. Wear self-contained breathing apparatus.	
Unusual fire or explosion hazards:	None identified.	
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.	

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	tal precautions: Do not allow product to enter sewer or waterways.		
Clean-up methods:	Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Store in a partly filled, closed container until disposal. Spilled material will solidify. Scrape up as much material as possible. Maintain good ventilation for large spills.		
	7. HANDLING AND STORAGE		
Handling: Do not handle contact lenses until all sealant has been removed f Residual sealant may transfer to lenses and cause eye irritation. A with eyes, skin and clothing. Keep out of the reach of children. Pro moisture. Use only with adequate ventilation.			
Storage:	For safe storage, store between -20 °C (-4°F) and 40 °C (104°F) Store in a cool, dry area. Avoid moisture.		

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone 10 mg/m3 TV dust.		5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Phthalate ester	None	None	None	None
Silane derivative	None	None	None	None
	None	None	None	None
Reactive Silane	None	None	None	None

Engineering controls:

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure $\ensuremath{\mathsf{limit}}(s).$

Eye/face protection:

Skin protection:

Safety goggles or safety glasses with side shields.

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: . Vapor pressure: **Boiling point/range:** Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:** Viscosity: Decomposition temperature:

Liquid Various Alcohol Not available. Not applicable Not applicable Not applicable Not applicable 1.4 - 1.5 at 20 °C (68°F) Heavier than air. 107 °C (224.6 °F) Seta closed cup Not available. Not available. Not applicable Not applicable Insoluble Not available. 2.48 %; 36 g/l (Calculated, as packaged) Not available. Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Methanol is liberated slowly upon exposure to moisture.
Incompatible materials:	Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Exposure to moisture.
	11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Inhalation, Skin contact, Eye contact

Potential Health Effects/Symptoms

Inhalation:	May be harmful if inhaled. Methanol is released during application and cure, which may affect the nervous system causing dizziness, headache or nausea.
Skin contact:	Prolonged or repeated contact with uncured sealant may cause skin irritation.
Eye contact:	Vapors may irritate eyes. Contact with eyes will cause irritation. Symptoms include itching, burning, redness and tearing.
Ingestion:	Harmful if swallowed. Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Limestone	None	Nuisance dust	
Phthalate ester	None	Irritant	
Silane derivative	None	Irritant, Allergen	
	None	No Data	
Reactive Silane	None	Irritant, Allergen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Phthalate ester	No	No	No
Silane derivative	No	No	No
	No	No	No
Reactive Silane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability,

corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (4 Proper shipping name: Hazard class or division: Identification number: Packing group:	9 CFR) Not regulated None None None
International Air Transportation (ICAO/IATA) Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None
Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:	Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis Delayed Health, Immediate Health None above reporting de minimis
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s):

3, 8, 11, 15

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date: 01/09/2015

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.