
Pinnacle Sun



Cool Roof Technology that Fights Smog



Pinnacle® Sun shingles are where function meets beauty. With protection against harsh sunshine, smog, algae, and high winds; you're investing in a durable roofing system that is built to last.



Length: 42" / 1066.8 mm Width: 14" / 355.6 mm

Exposure: 6" / 152.4 mm Shingles Per Bundle: 18-20

FEATURES

Available In 6 Colors

3M™ Scotchgard™ Protector

Class 3 Impact Rating

3M™ Cooling Technology

3M™ Smog-Reducing Technology

130 mph Wind Limited Warranty**

FASTAC® Double Sealant Lines

Atlas Lifetime* Algae Resistance

Limited Warranty

Lifetime Limited Warranty**

Atlas Signature Select® Eligible¹

ASTM

D7158, Class H Wind Resistance, Passed at 150 mph D6381, Uplift Resistance D3018, Type 1 D3161, Class F, Tested at 110 mph D3462, As Manufactured E108, Class A Fire Resistance E1980, Solar Reflectance

Signature Select®

For maximum protection and warranty coverage, install an Atlas Signature Select® Roofing System with components designed and backed by an Atlas warranty.

UL

790, Class A Fire Resistance 2218, Class 3 Impact Resistance 2390, Class H Wind Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product Control Approved

SAFETY, STORAGE AND HANDLING

WARNING: Roofing application can be dangerous. Observe all precautions and safety guidelines in accordance with proper roofing trade practices. Minimize roof traffic. Perform regular roof maintenance in appropriate weather.

IMPORTANT PRECAUTIONS: Store on flat surface. Protect from weather during storage and on job site. Sealant protection tape is placed on back of each shingle and does not have to be removed before applying.

For additional safety, storage, and handling instructions go to: AtlasRoofing.com/roof-shingles/sds

INSTALLATION AND SPECIFICATIONS

For warranty and installation instructions go to: **AtlasRoofing.com/roof-shingles/pinnacle-sun**For detailed installation and complete 3-part specifications go to: **AtlasRoofing.com/roof-shingles/specifications**

Allas Roofing Corporation (ATLAS) warrants to you, the original owner of its shingle products, that this product is free from any manufacturing defects that materially affect the performance of your shingle during the Premium Protection Period or that cause leaks for the balance of the applicable warranty period.

- * In order to qualify for the Atlas Lifetime Algae Resistance Limited Warranty against black streaks caused by blue-green algae, installation must include StormMaster® Hip & Ridge shingles, Pro-Cut® Hip & Ridge shingles or Pro-Cut® High Profile Hip & Ridge shingles featuring Scotchgard™ Protector with Atlas shingles featuring Sc
- ** Refer to the Atlas Roofing Limited Shingle Warranty for all coverage requirements.
- Refer to the Atlas Signature Select® Limited Warranty for all system coverage requirements

Scotchgard™ and the Scotchgard™ Protector logo, including the plaid design and 3M™ logo, are all trademarks of 3M



AtlasRoofing.com #AtlasProtects

Pinnacle® Sun Colors







Cool Moonlight Beach



SRI: 18



Cool Surf





Cool Coral Canyon





SRI: 17



Cool Sand

SRI: 19



Don't worry. We've got you covered with the Atlas Lifetime Limited Warranty's ensuring your investment is protected for years to come.



Let those winds howl. Because of our innovative HP42® shingle technology, your roof is shielded from wind gusts up to 130 mph.



HP42® technology features a wide format for better curb appeal, plus our Sweet Spot™ nailing area and double FASTAC® sealant line ensure your shingles will stay put.



UL 2218 Class 3 impact resistance rating offers protection against harsh weather conditions, keeping your home safe and secure.



Your roof will stay beautiful because it features 3M™ Scotchgard™ Protector, which resists black streaks and stains caused by algae.



Controlling the power of the sun with $3M^{\mbox{\tiny M}}$ reflective granules, which will keep your roof and home up to 20° cooler, helping to reduce your energy expenses.



 $3M^{^{\!{}_{\!M}}}\operatorname{Smog-Reducing}\operatorname{Granules}$ use a patented photocatalytic coating converting harmful gases into washable plant-nutrient nitrates.

The Solar Reflectance Index (SRI) is an indicator of the ability of a roof surface to return solar energy to the atmosphere. Roofing material surfaces with a higher SRI will be cooler than surfaces with a lower SRI under the same solar energy exposure, especially on a sunny day. Using materials with higher SRI values can enhance building occupant comfort and reduce air conditioning use. For more information, please reference the Cool Roof Rating Council: https://coolroofs.org/



To provide homeowners with the most accurate representation of color options, several photo scans and house shots were used under various lighting conditions. Variations in lighting illustrate the color gradients on asphalt shingle roofs.

