



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

1 Identification

· Product identifier

· Trade name: SmartCoat 350 Silicone Mastic

· Other means of identification: No other identifiers

· Recommended use and restriction on use

· Recommended use: Non-Fibered Silicone Mastic

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

CertainTeed LLC 20 Moores Road Malvern, PA 19355 610 341 7000 9am-5pm EST-USA www.certainteed.com CertainTeed-EHS@saint-gobain.com

· Emergency telephone number:

ChemTel (800)255-3924 (North America) +1 (813)248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 2 H373 May cause damage to the nervous system through prolonged or repeated exposure.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





GHS07 GHS08

· Signal word: Warning

· Hazard statements:

H227 Combustible liquid.

H317 May cause an allergic skin reaction.

H373 May cause damage to the nervous system through prolonged or repeated exposure.

Precautionary statements:

P210 Keep away from flames and hot surfaces. – No smoking.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

(Cont'd. on page 2)

(Cont'd. of page 1)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

Trade name: SmartCoat 350 Silicone Mastic

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection.

P302+P352 If on skin: Wash with plenty of soap and water.
P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:				
13463-67-7	Titanium dioxide	≤10%		
	butan-2-one O,O',O''-(methylsilylidyne)trioxime STOT RE 2, H373 Eye Irrit. 2A, H319; Skin Sens. 1B, H317	≤5%		
13822-56-5	3-(trimethoxysilyl)propylamine Skin Irrit. 2, H315; Eye Irrit. 2A, H319 Flam. Liq. 4, H227	<5%		

· Additional information:

Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for TiO_{\square} note that the substance must be respirable.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Respiration of particulates is unlikely during normal usage.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Nausea in case of ingestion.

Gastric or intestinal disorders when ingested.

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

Trade name: SmartCoat 350 Silicone Mastic

(Cont'd. of page 2)

Allergic reactions

- Danger: May cause damage to the nervous system through prolonged or repeated exposure.
- Indication of any immediate medical attention and special treatment needed:

Treat symptomatically.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: Water stream.
- Special hazards arising from the substance or mixture

Combustible liquid.

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information: Cool endangered product with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid formation of dust.

Avoid breathing dust.

Use personal protective equipment as required.

Protect from heat

Remove ignition sources.

Take precautionary measures against static discharge.

- Environmental precautions Avoid release to the environment.
- Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

For large spills, absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Use only in well ventilated areas.

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

Trade name: SmartCoat 350 Silicone Mastic

(Cont'd. of page 3)

Avoid contact with the eyes and skin.

Open and handle receptacle with care.

Avoid breathing dust.

· Information about protection against explosions and fires:

Combustible liquid.

Keep ignition sources away.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Store in cool, dry conditions in well sealed receptacles.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:				
13463-67-7 Titanium dioxide				
PEL (USA)	Long-term value: 15* mg/m³ *total dust			
REL (USA)	See Pocket Guide App. A			
TLV (USA)	Long-term value: 10 mg/m³			
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B			
EV (Canada)	Long-term value: 10 mg/m³ total dust			
LMPE (Mexico)	Long-term value: 10 mg/m³ A4			

Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

Avoid breathing dust.

- · Engineering controls: No relevant information available.
- Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

A NIOSH approved dust respirator should be used for operations generating dust.

For large spills, respiratory protection may be advisable.

Protection of hands:

(Cont'd. on page 5)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

Trade name: SmartCoat 350 Silicone Mastic

(Cont'd. of page 4)



Protective gloves

Gloves are advised for repeated or prolonged contact.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection: Protective work clothing

Information on basic physical and chemical properties			
Appearance:			
Form:	Liquid		
Color:	White		
Odor:	Characteristic		
Odor threshold:	Not determined.		
pH-value:	Not determined.		
Melting point/Melting range:	Not determined.		
Boiling point/Boiling range:	Not determined.		
Flash point:	≥92 °C (≥197.6 °F)		
Flammability (solid, gaseous):	Not applicable.		
Auto-ignition temperature:	Not determined.		
Decomposition temperature:	Not determined.		
Danger of explosion:	Product does not present an explosion hazard.		
Explosion limits			
Lower:	Not determined.		
Upper:	Not determined.		
Oxidizing properties:	Non-oxidizing.		
Vapor pressure:	Not determined.		
Density:			
Relative density:	~1.47		
Vapor density:	Not determined.		
Evaporation rate:	Not determined.		
Solubility in / Miscibility with			
Water:	Soluble.		

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

Trade name: SmartCoat 350 Silicone Mastic

(Cont'd. of page 5)

· Viscosity

Dynamic: Not determined. Kinematic: Not determined.

• Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Excessive heat.

Prevent formation of dust.

- · Incompatible materials No relevant information available.
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- On the eye: Based on available data, the classification criteria are not met.
- · **Sensitization**: Sensitization possible through skin contact.
- · IARC (International Agency for Research on Cancer):

Reference to titanium dioxide is based on unbound respirable particles and is not applicable to the product as supplied.

13463-67-7 Titanium dioxide

2B

NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Eye contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

(Cont'd. on page 7)

Page: 7/9

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

Trade name: SmartCoat 350 Silicone Mastic

(Cont'd. of page 6)

(Cont'd. on page 8)

- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure:

May cause damage to the nervous system through prolonged or repeated exposure.

· Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

· Label

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · **Recommendation:** Disposal must be made according to official regulations.

14 Transport information				
· UN-Number	NIA 4000			
· DOT · ADR/RID/ADN, IMDG, IATA	NA1993 Not regulated.			
· UN proper shipping name · DOT	Combustible liquid, n.o.s. (3-(trimethoxysilyl)			
· ADR/RID/ADN, IMDG, IATA	propylamine) Not regulated.			
Transport hazard class(es)				
· DOT				
COMMONIAL				
· Class	3			

3

Page: 8/9

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

Trade name: SmartCoat 350 Silicone Mastic

 ADR/RID/ADN, IMDG, IATA Class Packing group DOT ADR/RID/ADN, IMDG, IATA Environmental hazards Marine pollutant: Special precautions for user Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Transport/Additional information: DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US gal / 450 L. 		(Cont'd. of page 7)		
Packing group DOT DOT DOT Not regulated. Environmental hazards Marine pollutant: No Special precautions for user Not applicable. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US	· ADR/RID/ADN, IMDG, IATA			
DOT III ADR/RID/ADN, IMDG, IATA Not regulated. Environmental hazards Marine pollutant: No Special precautions for user Not applicable. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US	Class	Not regulated.		
 ADR/RID/ADN, IMDG, IATA Environmental hazards Marine pollutant: No Special precautions for user Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Transport/Additional information: DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US 	· Packing group			
 Environmental hazards Marine pollutant: Special precautions for user Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Transport/Additional information: DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US 	· DOT	III		
 Marine pollutant: Special precautions for user Not applicable. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US 	· ADR/RID/ADN, IMDG, IATA	Not regulated.		
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. Transport/Additional information: DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US		No		
MARPOL73/78 and the IBC Code 'Transport/Additional information: 'DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US	· Special precautions for user	Not applicable.		
 Transport/Additional information: DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US 	Transport in bulk according to Annex II	Transport in bulk according to Annex II of		
· DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US	MARPOL73/78 and the IBC Code	Not applicable.		
Labeling is only required for single packages ≥119 US	· Transport/Additional information:			
	·DOT	Labeling is only required for single packages ≥119 US		

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to titanium dioxide is based on unbound respirable particles and is not applicable to the product as supplied.

13463-67-7 Titanium dioxide

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

(Cont'd. on page 9)

Page: 9/9

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 01, 2020

Trade name: SmartCoat 350 Silicone Mastic

(Cont'd. of page 8)

None of the ingredients are listed.

IARC (International Agency for Research on Cancer):

Reference to titanium dioxide is based on unbound respirable particles and is not applicable to the product as supplied.

13463-67-7 Titanium dioxide

2B

· Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Flam. Liq. 4: Flammable liquids – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtel.com