25-135H 13" Portable Planer w/Helical Style Cutterhead



MOTOR

WARRANTY	5 YEARS
Shipping Carton	24-3/4"x16"x20-1/4"
Shipping Weight	76 lbs.
Net Weight	68 lbs.
Base Size	22" x 13-3/8"
Depth	34-1/4″
Width	22″
Height	19-1/4″
OVERALL	
Extension Tables (2) (L x W)	12" x 14"
Table Size (L x W)	9-7/16" x 13-1/16"
Two Feed Speeds	16 & 26 SF/MIN
Minimum Thickness of Stock	3/16″
Minimum Width of Stock	3/4″
Minimum Length of Stock	7″
Maximum Cutting Depth (Height)	6″
Maximum Cutting Width	13″
Maximum Depth of Cut	1/8" within 6" wide
Insert Rows	1/16" @ 6"to 13"wide
Number of	6
HSS Insert Size	14.2mm x 14.2mm x 2mm
Number of HSS Inserts (2 Sided)	26
Speed	10,000 RPM
Diameter	2″
CUTTERHEAD	,
Minimum CFM Noise Level (No Load	
DUST PORT Dust Port (0.D.) Dust Collection	4" or 2-1/2" Diameter 650
•••••	10) 22,000
Volts Motor Speed (No Loa	115V, 60 Hz ad) 22,000
Amps	15
	45

WARRANTY **5 YEARS** 13" PORTABLE PLANER 25-135H features a six row helical-style cutter head and 26 HSS insert cutters. Each indexable knife insert is precision sharpened on two edges and can be easily changed/rotated if damaged or worn - just loosen, rotate, and retighten! The alternating cutter pattern in the cutter head is super-efficient, and with a two-speed feed rate, produces a smooth cut surface. Planer features a threaded 4-post threaded housing for extra head stability when running, side handle for guick table height adjustments, repeat cut setting lever, large fold-up extension tables, flat top with rollers for stock returning, and side carry handles.

FEATURES

- Powerful 15 AMP Motor
- Helical Style Cutterhead
- 2-Speed Feed Rate
- All Steel Construction
- Easy Blade Access
- Infeed/Outfeed Table Extensions

ACCESSORIES

MODEL	DESCRIPTION
25-499	HSS 2-Edge Inserts (10 Pack) 14.2mm x 14.2mm x 2mm
25-499C	Carbide 2-Edge Inserts (10 Pack) 14.2mm x 14.2mm x 2mm
25-498	Mounting Screws T25 (10 Pack) for Inserts 25-499, 25-499C
23-901	Flexible/Expandable Roller Stand





DUST PORT OUTLET PROVIDES EASY CONNECTION





SETTING GAUGE

EASY ACCESS TO CUTTERHEAD TO CHANGE INSERT BLADES

