## RIKON

## 1HP Dust Collector

**Model 60-101** 



MOTOR	
Horsepower	1 HP TEFC
Inverter	Input 1Ph, Output 3Ph
Amps	7 A / 3.5 A, 60 Hz, 1 Ph
Volts	120 V / 240 V
Speed	3,450 RPM
Velocity	800 @ 4" or 1,100 @ 5" inlet

Blower	
Blower Impeller	10" Diameter, Aluminum
Sound Rating @ 6 Feet	<86.375 dB



Filtration	
Canister Filtration Rating	1 Micron
Filtration Efficiency	99%
Filter	
Canister Pleated Filter Size	19-5/8" x 7-1/8"
Filter Cleaning Method	Hand crank, internal rotating flapper
Additional Specs	
Plastic Bag Length (installed)	20"
Plastic Bag Capacity	1.5 Cu. Ft.
Dust Ports / Hose Connections	1 @ 5", 2@4"
Intake Funnel Size	5" diameter
Machine Certification	CSA
Construction	All metal frame



OVERALL DIMENSIONS	
Length	46"
Depth	21"
Height	23-1/2"
Net Weight	61 lbs.
Shipping Weight Box 1of 2	45.2 lbs.
Shipping Carton Box 1of 2	18.6" x 18.3" x 15.8"
Shipping Carton Box 2 of 2	22" x 22" x 17.32"
Shipping Weight Box 2 of 2	23.2 lbs.







**Model 60-101** 

## **1HP Dust Collector Features**



## 1 HP Wall Mounted Dust Collector is perfect for small shops that have limited floor space.

Mounting this powerful dust collector on a wall near your most used machines is ideal for always having it connected and operating while you work.

The 10" spiral impeller creates big CFM suction to whisk away the wood chips and dust from bandsaws, planers, jointers or sanders – 800 CFM with 4" or 1,100 CFM with 5" inlet. A dual 4" inlet fitting with cover cap permits the collector to be connected to 1 or 2 machines.

Just cap one of the inlets for full air drawing power on one machine, then easily switch inlets to use with the other machine! Polyester spun bond pleated canister filter includes an internal flapper to clean its air filtering fabric.

Just turn the units side handle to activate the cleaner! All the wood collection debris falls into the bottom clear plastic bag, which is easy to dispose. Dust Collector includes wall mounting bracket, pleated canister filter with cleaning handle assembly, disposable plastic dust bag, strap clamp, dual 4" inlet fitting, 4" inlet cap, on/off safety switch and instruction manual.

