62-450 Air Filtration System 450 CFM



EYE BOLTS

1/4 HP
1.5
120V, 60Hz
250, 350, or 450 CFM
450 CFM
9-1/2" x 16-1/2" x 2"
Outer 5, Inner 1
68 dB on High
1, 2, or 4 Hour Segments
20' x 20' x 8' Room 8 Times Per Hour
20 Gauge Steel
Steel
Squirrel Cage
19-3/4"

16-3/4"

28.5 lbs.

32.5 lbs.

5 YEARS

23-1/4" x 20" x 13"

10"

1/4 HP AIR FILTRATION SYSTEM 62-450 is very effective for smaller sized shops with its air flows of 250, 350 or 450 CFM. For large rooms up to 20' x 20' x 8' with average dust creation from work, this unit will circulate and clean the air 8 times per hour. Unit includes fuse overload protection.

FEATURES

- Sturdy 20 Gauge **Steel Cabinet Construction**
- Three Speed Settings of 250, 350, 450 CFM
- Three Timer Settings
- Settings Via Push Buttons or **Remote Control**
- Ouick Release Latches for **Easy Filter Changes**
- Replaceable Inner and Outer Filters
- Eye Bolts for Ceiling Mounting
- Top Carry Handle for Easy Moving the System Around the Shop

ACCESSORIES

MODEL	DESCRIPTION
62-901F	Outer Filter 9-1/2" x 16-1/2" SEP Pleated, 5 Micron
62-902F	Inner Filter Bag 9-1/2" x 16-1/2", 1 Micron






OUICK LATCH SYSTEM FOR CHANGING FILTERS



OUTER FILTER 9-1/2" X 16-1/2" SEP PLEATED, 5 MICRON



ACCESSORY 62-902F INNER FILTER BAG 9-1/2" X 16-1/2". 1 MICRON



HOW AIR MOVES THROUGH TWO STAGE **AIR FILTRATION SYSTEM**

Width

Height

Net Weight

Shipping Weight

Shipping Carton

WARRANTY