

The World's Finest Portable Rollforming Equipment



SSR[™] Roof Panel Machine



Light Commercial / Residential Roof Panel Machine

The state-of-the-art SSR MultiPro Jr.™ Panel Machine runs up to 9 panel profiles in variable widths, multiple gauges and various material types.


	STANDARD FEATURES				
•	Polyurethane Drive rollers	•	Mechanically-seamed profiles include 1 single-lock hand seamer		
	Length Control Limit Switch		100 foot, 10 gauge, 20 Amp Extension Cord		
	Waterproof NEMA 4 Electrical System		20' of Run Out Table		
	Forward Pulling, Easy Cut Shear	•	One Expandable Arbor / Reel		
•	Push Button RUN/JOG Controls at Entry and Exit Ends	•	Welded Tubular Steel Frame		
•	Choice of: EZE-Change™ Profile Roller System		UL 90 Rated Panels (must be certified by UL for recognition)		
	Choice of: 1 Pair of Bead, Pencil, Striation, or V-Rib Rollers		Industry's Best Warranty		
	Dual Overhead Reel Rack				

OPTIONS			
TR12 – 12,000 lb. (5,500 kg) Capacity NATM Compliant Tandem Axle Trailer, with Crane Lifting Eyes, Four-Drop Foot Stabilizing Jacks and Elec. Brakes with Breakaway Kit	EZC-P – EZ-Counter Computerized Length Controller		
CRV-SSR – Machine Cover	ELEC1 – 1.5 Hp, 120VAC, 60 Hz, 1Ph, 18 Amps		
DR01-EX – Expandable Arbor (16" to 20" ID) (400mm - 500mm)	ELEC2 – 1.5 Hp, 220VAC, 60 Hz, 1Ph, 9 Amps		
ROSR10 – 10' (3m) Sections of Variable Height Run Out Table	ELEC3 – 1.5 Hp, 220VAC, 50 Hz, 1Ph, 9 Amps		
RR1 – Bead Rollers	REM-2-A – 2-Button Wireless Remote Control (Start/ Stop)		
RR2/4 – Pencil Rib Rollers (Large/Small)	FSD1 – Single Free Standing Decoiler		
RR3/5 – V-Rib Rollers (Large/Small)	HS1 – Additional single Lock Hand Seamer for SSR100 and SSR150 mechanically seamed profiles		
RR6 – Striation Rollers			

SPECIFICATIONS					
SSR PANEL MACHINE • Length 12'10" (3.9m) • Width 3'10" (1.2m) • Height 4'3" (1.3m) w/ Over Head Rack 1'10" (.6m) w/o Over Head Rack • Weight 2275 lbs. (1000kg)	 MATERIALS FORMED Painted Steel 28 ga. to 24 ga. (0.4mm to 0.6mm) (painted, galvanized, aluminized) Painted Aluminum .027" to .040" (0.7mm to 1.0mm) Copper 16 oz. to 20 oz. 3/4 Hard (0.5mm to 0.7mm) 				
SSR ON TRAILER • Length 17'6" (5.3m) • Width 7' (2.1m) • Height 6'3" (1.9m) with reel • Weight 3975 lbs. (1700kg)	Manually Powered, Infinitely Adjustable, Hardened Tool Steel Blades and Dies				
COIL WIDTH • 15" to 20" (380mm to 508mm)	• Electrically Driven Polyurethane Rollers				
FINISHED PANEL WIDTHS • 12" to 16" (305mm to 406mm)	SPEED 30 ft./min (9m/min) Approx.				

PROFILES				
U-Panel	1/2" to 1-1/2" high (12.7mm to 38.1mm)			
SSR100*†	1" high x 1/2" wide (25.4mm x 12.7mm) mechanically seamed panel. Includes a hand seamer.			
SSR150*†	1-1/2" high x 1/2" wide (38.1mm x 12.7mm) mechanically seamed panel. Includes a hand seamer.			
SSR450 / 450SL*	1-1/2" high x 1/4" wide (38.1mm x 6.4mm) snap clip panel/snap lock panel.			
FFR100	1" snap seam (25.4mm) with slotted fastener flange for clipless installation. Includes clip relief rollers and automatic "no chip" rotary slotter.			
FFR150	1 - 1/2" snap seam (38.1mm) with slotted fastener flange for clipless installation. Includes clip relief rollers and automatic "no chip" rotary slotter.			
SSRBP	1" or 1-1/2" leg (25.4 or 38.1mm) Bermuda Panel			

- * Can make U-Panel
- † Suitable for Zinc
- All roller systems include shear dies & clip relief rollers.
- SSR100, SSR150 and SSR450/450SL and SSRBP Roller Systems all use identical left side roller sets.
- FFR100 and FFR150 also share identical left side roller sets.
 If you purchase or own one of these roller systems, you can add any of the right side systems at a reduced price!



Options



Machine w/Cover



EZ-Counter Computeria Length Controller



UL mark not recognized until certified by UL

Standard Trailer



Run Out Table



2-Button Remote Control (start and stop)



Free Standing Decoiler (Arbor NOT included)

Warranty

- · Three years parts / Three years labor (including electrical)
- · Limited lifetime separation on drive rollers
- · Limited lifetime on stainless steel forming rollers

U.S. PATENT NO. 6,772,616