



Installation Instructions

QuickRail® 45-Degree Bracket Adapters

General & Safety Information

- Wear proper personal protective equipment (PPE).
- Operate all tools per manufacturer guidelines.
- Standard woodworking saws and blades can be used for cutting Fypon® PVC products, except in cases where metal is being cut.
- These instructions only refer to installing bracket adapters for a rail kit, and they assume that correctly specified posts are already properly installed, per code requirements.
- Consult your local building department for applicable codes and building requirements.
- All Fypon products must be installed per the following instructions to maintain warranty coverage.
- Do NOT paint or stain QuickRail products, it will void the warranty.

Tools / Materials

- Pencil
- Tape measure
- Level

Kit includes:

- (2) Top Rail 45-Degree Bracket Adapters
- (2) Bottom Rail 45-Degree Bracket Adapters
- (8) 2" Screws

Installation Instructions

These instructions are supplemental to the QuickRail Straight Rail Installation Instructions, and refer only to the additional steps needed when installing 45-degree bracket adapters. DO NOT use with multi-angle brackets.


1) Install bottom mounting brackets and adapters.

Identify top and bottom 45-degree bracket adapters (Figure 1A). Follow the rail kit instructions and install the bottom mounting bracket and bottom adapter at the same time, using the 2" screws provided with the adapter kit (Figure 1B).


2) Install top mounting brackets and adapters.

Follow the rail kit instructions and install the top mounting bracket and top adapter at the same time, using the 2" screws provided with the adapter kit (Figure 2).

Figure 1A




Top rail bracket adapter




Bottom rail bracket adapter

Figure 1B



Bottom mounting bracket and adapter

Figure 2



Top mounting bracket and adapter