

## Specifications

Catalog #						Description						
Rivet Dia.	Steel Rivet Plated Steel Mandrel	Aluminum Rivet Aluminum Mandrel	Aluminum Rivet Plated Steel Mandrel	Stainless Rivet Stainless Mandrel	Copper Rivet Plated Steel Mandrel	Hole Size	Drill No.	RL (Rivet Body Length)	RD (Rivet Body Diam.)	HW (Rivet Head Width)	HT (Rivet Head Thickness)	Grip Range
1/8"	SS42D	AA42D	AS42D	SS/SS42D	CS42D	.128-.132	#30	.232	.125	.250	.032	.063-.125
1/8"	SS43D	AA43D				.128-.132	#30	.294	.125	.250	.032	.126-.187
1/8"	SS44D	AA44D	AS44D	SS/SS44D	CS44D	.128-.132	#30	.357	.125	.250	.032	.188-.250
1/8"	SS46D	AA46D		SS/SS46D		.128-.132	#30	.481	.125	.250	.032	.313-.375
1/8"		AA48D		SS/SS48D		.128-.132	#30	.606	.125	.250	.032	.376-.500
1/8"	SS42DW*	AA42DW*				.128-.132	#30	.232	.125	.250	.032	.063-.125
1/8"	SS44DW*	AA44DW*				.128-.132	#30	.357	.125	.250	.032	.188-.250
3/16"	SS62D					.192-.196	#11	.277	.187	.375	.047	.020-.125
3/16"	SS64D	AA64D				.192-.196	#11	.402	.187	.375	.047	.188-.250
3/16"	SS66D					.192-.196	#11	.527	.187	.375	.047	.251-.375

\* White painted rivets

## Specifications

<b>Rivet Mandrel</b>	<b>Rivet</b>	<b>Minimum Shear</b>	<b>Lbs. Tensile</b>
Steel Rivet Steel Mandrel	1/8" 3/16"	260 540	310 680
Aluminum Rivet Aluminum Mandrel	1/8" 3/16"	120 260	150 320
Aluminum Rivet Steel Mandrel	1/8" 3/16"	120 260	150 320
Stainless Rivet Stainless Mandrel	1/8" 3/16"	420 950	530 1200
Copper Rivet Steel Mandrel	1/8"	350	450