

# NOVABOND

## Hybrid Construction Sealant



NBP100  
WHITE



NBP105  
ANTIQUE WHITE



NBP107  
CANVAS




NBP140  
BEIGE




NBP191  
MONTEREY SAND




NBP146  
SANDSTONE




NBP159  
LIMESTONE




NBP3515  
CAPE COD GRAY




NBP134  
TERRATONE




NBP182  
RED ROCK




NBP193  
COCOA BEAN



NBP120  
DARK BRONZE



NBP162  
FOREST GREEN




NBP110  
BLACK

Colors shown for illustrative purposes. Verify product color match before applying.

# NOVABOND<sup>TX</sup>ure

## Textured Hybrid Construction Sealant

Also available in a textured formula to complement mortar, brick, stone, concrete, asphalt, and stucco applications.



Available in standard mortar colors: White, Beige, Limestone, Cape Cod Gray, Dark Bronze, and Black. Contact your representative for current color availability.

- Excellent adhesion
- Permanently flexible
- Paintable in 1 hour
- Extrudes down to -10°F
- Adheres to:
  - Metal
  - Wood
  - Masonry
  - PVC
  - PVDF
  - Asphalt Shingles
  - Common Construction Materials

Made in USA. Professional Grade.



# NOVA BOND

## Hybrid Construction Sealant Textured Hybrid Construction Sealant

### Product Specifications

Physical Property	Test Method	Smooth Performance Range	TXtUre Performance Range
Appearance		Smooth Paste	Textured Paste
Skin Over Time	3/8" @ 50% RH & 77°F	15-45 Minutes	15-45 Minutes
Through Cure	3/8" @ 50% RH & 77°F	7 days	7 days

### Typical Properties\*

Physical Property	Test Method	Smooth Typical Value	TXtUre Typical Value
Specific Gravity		1.4 - 1.5	1.4 - 1.5
Tensile Strength	ASTM D412	300 psi	220 psi
Elongation	ASTM D412	300%	200%
Shore Hardness	ASTM D2240	45 +/- 5	45 +/- 5
Adhesion	ASTM D903		
Aluminum		15 pli	15 pli
Wood		15 pli	15 pli
PVC		14 pli	14 pli
Joint Movement	ASTM C719	+/- 35	+/- 25

\*The values outlined reflect testing that was conducted under laboratory conditions, actual results may vary. The information provided in the above table is not intended for use in preparing specifications. Please consult manufacturer for additional information.

### Paintable in 1 Hour

- Permanently flexible
- Will not shrink or crack
- Waterproof
- Mold/Mildew resistant
- UV resistant

### Interior and Exterior Applications

- Excellent adhesion to most building substrates
- Will not sag or slump
- Tack-free in 15-45 minutes
- Completely cured within 5-7 days

### Easily Gunned at all Temperatures

- Weatherproof plastic cartridges with removable tips
- Excellent tooling properties

### VOC Compliant in all 50 States (Green Building Compliant)

- California Proposition 65 Compliant
- Low odor
- Solvent free

### AAMA Verified for Window Installs (smooth paste)

- Will not freeze
- 18 month shelf life
- Available in all major siding, trim coil, and window manufacturer colors

### Professional Grade



**NOVAGARD**

Sealants | Foams | Coatings | Thermals

5109 Hamilton Avenue  
Cleveland, OH 44114 USA  
(216) 881-8111 | (800) 380-0138  
(216) 881-6977 fax  
novagard.com

ISO 9001:2015 (QMS with Design)  
IATF 16949:2016 (QMS with Design)

NovaBond is proudly  
made in Cleveland, OH  
Effective Date: May 2019-v2.0