

RIKON

NEW

14" Bandsaw Model 10-324TG

13" Cutting Capacity

Quickly adjust your cutting height up to 13". Comes with Quick Reference Scale on Guard




6" Tall Fence

Quick adjusting fence and re-saw bar



NEW Tool-less Thumbscrew Bearing Locks

No tools needed to adjust guide bearings



NEW Longer Fence Rail

Heavy duty steel rail 29" long



Specifications

| MOTOR | | BLADE | | OVERALL DIMENSIONS | |
|------------------|----------------|------------------|--------------------------|--------------------|-------------------|
| Horsepower | 1-1/2 HP TEFC | Width | 3/16" - 3/4" | Height | 75" |
| Amps | 14/7 | Length | 111" | Width | 30" |
| Volts | 115/230V, 60Hz | Blade Speed | 1,445/2,950 FT/MIN | Depth | 25" |
| | | Includes | 111" x 5/8", 4 TPI, Reg. | Base Size (WxD) | 21-5/8" x 14-3/4" |
| | | | | Dust Port | 1@4" |
| CUTTING CAPACITY | | TABLE | | Net Weight | 219 lbs. |
| Height | 13" | Size | 21-1/2" x 15-3/4" | Gross Weight | 231 lbs. |
| Width | 13-5/8" | Left Tilt | -5° | Shipping Width | 17-1/2" |
| | | Right Tilt | 45° | Shipping Depth | 23-5/8" |
| | | Miter Gauge Slot | (2) 3/4" x 3/8" | Shipping Height | 54" |
| | | Height to Floor | 39-1/2" | | |

Call today for more information **877-884-5167**
or visit **www.rikontools.com** for a dealer near you!



RIKON

NEW

Available Accessories



Foot
Pedal
Design

Optional 13-326 Mobility Kit
(Must be used with optional 13-324 base plate adapter)

Make It Mobile

BANDSAW BLADES

| Length | Width | Gauge | TPI | Style | Item No. |
|--------|-------|-------|-----|------------|----------|
| 111" | 3/16" | .025" | 10 | Reg. Tooth | 19-1101 |
| 111" | 1/4" | .025" | 6 | Hook Tooth | 19-1100 |
| 111" | 3/8" | .025" | 4 | Hook Tooth | 19-1102 |
| 111" | 1/2" | .025" | 3 | Hook Tooth | 19-1103 |
| 111" | 5/8" | .025" | 3 | Hook Tooth | 19-1104 |
| 111" | 5/8" | .025" | 4 | Reg. Tooth | 19-1105 |

Bi-Metal

| | | | | | |
|------|------|-------|-------|------------|---------|
| 111" | 1/2" | .025" | 14 | Reg. Tooth | 19-1511 |
| 111" | 1/2" | .025" | 18 | Reg. Tooth | 19-1512 |
| 111" | 3/4" | .035" | 8/12 | Var. Tooth | 19-1513 |
| 111" | 3/4" | .035" | 10/14 | Var. Tooth | 19-1514 |

ACCESSORIES

| | |
|---------|--|
| C10-109 | Replacement Guide Bearings (Pack of 6) |
| 13-324 | Base Plate Adapter (Must be used with 13-326 mobility kit) |
| 13-326 | Mobility Kit (Must be used with 13-324 base plate adapter) |
| C10-391 | Table Inserts (Pack 4) |
| C10-392 | Zero Clearance Insert (Pack 4) |
| C10-395 | Aluminum Insert |
| 13-912 | Miter Gauge 3/4" x 3/8" T-Slot |
| C10-995 | Replacement Drive Belt |
| 12-201 | LED Gooseneck Worklight with Magnetic Base & Magnetic Clip |

Call today for more information **877-884-5167**
or visit **www.rikontools.com** for a dealer near you!

